

choosing the right product for your **installation**

- Above Grade Plywood / OSB All BR-111™ Products
- On-Grade Plywood / OSB All BR-111™ Products
- On-Grade Concrete 5/16” & 7/16” Solids and All Engineered Products
- Below Grade Concrete All Engineered Products

Product Installation Guidelines

	Nail / Staple	Glue-Down	Float
3/4” Solid	✓ 15 lb. Felt Underlayment	✗ Do Not Glue-Down	✗ Do Not Float
5/16” and 7/16” Solid	✓ 6 Mil Poly Required	✓ Moisture Cured Urethane Adhesive	✗ Do Not Float
3/8” Engineered	✓ 6 Mil Poly Required	✓ Moisture Cured Urethane Adhesive	✓ Two In One Floating Pad
5/16” Engineered	✗ Do Not Nail or Staple	✓ Moisture Cured Urethane Adhesive	✓ Two In One Floating Pad

Glue-Down Installation

Prior to installation concrete slabs must be tested for moisture. BR-111™ highly recommends the use of a moisture protection system available from the adhesive manufacturer, especially when gluing thinner 5/16” and 7/16” solid products to concrete slabs. Engineered products provide greater dimensional stability and may not require a moisture protection system, if tests reveal a dry slab. **BR-111™ does not warrant its products against moisture intrusion.**